

## YourHome Solar Ground Light

YOURHOME SOLAR GROUND LIGHT  
0054047



### Product features

- High quality inground solar light with twin LED lights and external solar panel
- Integrated daylight sensors
- Automatic light management - light up automatically when it gets dark after detecting any motion
- Easy installation - plug and play solution
- High lumen output - 56lm x 2
- Long rated lifetime - 25,000 hours
- ON/OFF switch
- Robust construction - stainless steel and ABS housing
- Perfect for gardens, flower beds, pathways, tree lighting
- Colour temperature - Cool White 4000K
- Operating temperature: -10°C to 40°C



### PRODUCT OVERVIEW

Product name	YOURHOME SOLAR GROUND LIGHT
Technology	LED
Cap/Base	N/A
Housing	ABS Plastic, Stainless steel
Mount	Ground mounted, Ground recessed
General application	Residential & Consumer
ETIM Class	N/A
Warranty	3 years
Fixture luminous flux (lm)	112
Luminaire efficacy (lm/W)	56
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	100
Photobiological Risk Group	RG1
Electrical protection	Class III
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Housing colour	Black
IP rating	IP65
IK rating	IK04
Product EAN number	5410288540474

### DATA TABLE

#### General data

Product name	YOURHOME SOLAR GROUND LIGHT
Technology	LED
Cap/Base	N/A

## YourHome Solar Ground Light

*YOURHOME SOLAR GROUND LIGHT*  
0054047

Housing	ABS Plastic, Stainless steel
Mount	Ground mounted, Ground recessed
General application	Residential & Consumer
Operating temperature range (°C)	-10°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	N/A
Warranty	3 years

### Optical data

Fixture luminous flux (lm)	112
Luminaire efficacy (lm/W)	56
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	100
Distribution type	Diffuse
Photobiological Risk Group	RG1

### Electrical data

Electrical protection	Class III
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	350
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	N/A

### Lifetime data

Lifespan L70 B50	30000
------------------	-------

### Physical data

Housing colour	Black
IP rating	IP65
IK rating	IK04
Diffuser finish	Diffuse
Diffuser material	Glass
Nominal Product Height (mm)	45
Nominal Product Diameter (mm)	120
Weight (kg)	1.216

### Packaging

Single packaging type	Carton
Product EAN number	5410288540474
Packaging single length / height (cm)	25.0
Packaging single width (cm)	23.0
Packaging single depth (cm)	8.5
DUN14 (outer)	15410288540471

## YourHome Solar Ground Light *YOURHOME SOLAR GROUND LIGHT* 0054047

Units per outer package	6
Packaging outer length / height (cm)	52.3
Packaging outer width (cm)	25.3
Packaging outer depth (cm)	28.3

### Safety data

Optimal operating condition (°C)	-10-40
----------------------------------	--------

## TECHNICAL DRAWINGS

