

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific information for OEL

BOSTIK ARDACOLOR FLEX MEDIUM GREY

Supercedes Date: 19-Mar-2020

Revision date 30-Apr-2020

Revision Number 1.03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name BOSTIK ARDACOLOR FLEX MEDIUM GREY

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Fillers, putties, plasters, modelling clay. Joint sealants.

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik BV De Voerman 8 PO Box 303

5215 MH's-Hertogenbosch, The Netherlands

Tel: +31 736 244 244 Fax: +31 736 244 344

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone No information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 1 - (H318)
Specific target organ toxicity (single exposure)	Category 3 - (H335)

2.2. Label Elements

Contains: Cement, portland, chemicals (Chromium VI reduced)



Signal word DANGER

Hazard statements

H315 - Causes skin irritation.

Europe - BE Page 1/10

Revision date 30-Apr-2020

BOSTIK ARDACOLOR FLEX MEDIUM GREY

Supercedes Date: 19-Mar-2020 Revision Number 1.03

H318 - Causes serious eye damage.

H335 - May cause respiratory irritation.

Precautionary statements

P102 - Keep out of reach of children.

P261 - Avoid breathing dust.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor.

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap.

P332 + P313 - If skin irritation occurs: Get medical advice/attention.

P501 - Dispose of contents/ container to an approved waste disposal plant.

Additional information

Cement product for which the amount of chromium VI was decreased to < 0,0002 % by a reduction agent (related to the total dry weight).

2.3. Other Hazards

When cement reacts with water a strong alkaline solution is produced. Prolonged contact with wet cement or wet concrete may cause serious burns because they develop without pain being felt e.g. when kneeling in wet cement even when wearing trousers

Frequent inhalation of large quantities of cement dust over a long period of time increases the risk of developing lung disease

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT) This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB)

SECTION 3: Composition/information on ingredients

3.1 Substances

Mixture

3.2. Mixtures Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Cement, portland, chemicals (Chromium VI reduced)	266-043-4	65997-15-1	40 - <80	STOT SE 3 (H335) Skin Irrit. 2 (H315) Eye Dam. 1 (H318)		Exempt

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Europe - BE Page 2/10

BOSTIK ARDACOLOR FLEX MEDIUM GREY

SECTION 4: First aid measures

Supercedes Date: 19-Mar-2020

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand.

Inhalation IF INHALED: Remove to fresh air and keep at rest in a position comfortable for

breathing. If symptoms persist, call a doctor.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Revision date 30-Apr-2020

Revision Number 1.03

Skin contact Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical

attention if irritation develops and persists.

Ingestion Do NOT induce vomiting. Clean mouth with water. Drink 1 or 2 glasses of water. Call a

doctor or poison control centre immediately.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Causes serious eye damage. Inhalation of dust in high concentration may cause irritation

of respiratory system. Irritating to skin.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Product itself does not burn.

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid generation of dust. Do not breathe dust. Use personal protective equipment as

required. Do not get in eyes, on skin, or on clothing.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Europe - BE Page 3/10

BOSTIK ARDACOLOR FLEX MEDIUM GREY

6.2. Environmental precautions

Supercedes Date: 19-Mar-2020

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containmentCover powder spill with plastic sheet or tarp to minimise spreading and keep powder dry.

Prevent dust cloud.

Methods for cleaning upTake up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Avoid generation of dust. Use personal protective

equipment as required. Do not breathe dust. Avoid contact with skin, eyes or clothing.

Revision date 30-Apr-2020

Revision Number 1.03

General hygiene considerations Keep away from food, drink and animal feedingstuffs. Do not eat, drink or smoke when

using this product. Wash hands before breaks and immediately after handling the

product. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep the packing dry and well sealed to prevent contamination and absorption of

humidity. After absorption of moisture or exceeding the shelf life the reducing agent for

chromate will lose its efficiency and sensitisation by skin contact may occur.

7.3. Specific end use(s)

Specific Use(s)

Fillers, putties, plasters, modelling clay. Joint sealants.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Quartz	TWA: 0.1 mg/m ³
14808-60-7	

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available.

Europe - BE Page 4/10

BOSTIK ARDACOLOR FLEX MEDIUM GREY

Supercedes Date: 19-Mar-2020 Revision Number 1.03

(PNEC)

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166

Hand protection Wear suitable gloves. Gloves must conform to standard EN 374. Recommended Use:.

Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove

Revision date 30-Apr-2020

material is in general greater than 480 min. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Unsuitable gloves materials:. Leather.

Skin and body protection Wear suitable protective clothing.

Respiratory protection Avoid generation of dust. Ensure adequate ventilation, especially in confined areas. In

case of insufficient ventilation, wear suitable respiratory equipment. Particle filter device

(DIN EN 143)

Recommended filter type: High efficiency particulate air filter. White. with filter for particulates.

Environmental exposure controls Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Powder
Colour Grey

Odour Slight Characteristic
Odour threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No data available

pH (as aqueous solution) > 11

Melting point / freezing point

Boiling point / boiling range

No data available

No data available

Flash point - °C

Evaporation rate No data available Flammability (solid, gas) No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressure No data available Vapour density No data available Relative density No data available Miscible in water Water solubility Solubility(ies) No data available **Partition coefficient** No data available Autoignition temperature No data available **Decomposition temperature** No data available Kinematic viscosity No data available Dynamic viscosity No data available **Explosive properties** No data available **Oxidising properties** No data available

9.2. Other information

Solid content (%) No information available

Europe - BE Page 5/10

Revision date 30-Apr-2020

Revision Number 1.03

BOSTIK ARDACOLOR FLEX MEDIUM GREY

Supercedes Date: 19-Mar-2020

VOC Content (%) No information available Density No information available

Bulk density 1.35 g/cm³

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion Data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information .

Inhalation Inhalation of dust in high concentration may cause irritation of respiratory system.

Eye contact Causes serious eye damage.

Skin contact Causes skin irritation.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. May cause redness and tearing of the eyes.

Numerical measures of toxicity

Acute Toxicity

Europe - BE Page 6/10

BOSTIK ARDACOLOR FLEX MEDIUM GREY

Supercedes Date: 19-Mar-2020

Revision date 30-Apr-2020

Revision Number 1.03

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Cement, portland, chemicals (Chromium VI reduced) 65997-15-1		>2000 Kg/mg (Lapin)	>5 g/m³ (Rattus)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity .

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation No information available.

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The components in this formulation do not meet the criteria for classification as PBT or

vPvB.

Europe - BE Page 7/10

BOSTIK ARDACOLOR FLEX MEDIUM GREY

12.6. Other adverse effects

Supercedes Date: 19-Mar-2020

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Dispose of contents/container in accordance with local, regional, national, and

Revision date 30-Apr-2020

Revision Number 1.03

international regulations as applicable.

Contaminated packagingDo not reuse empty containers. Handle contaminated packages in the same way as the

product itself.

European Waste Catalogue 17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09

01, 17 09 02 and 17 09 03

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN NumberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing GroupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

IMDG

14.1 UN numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated

14.5 Marine PollutantNp14.6 Special ProvisionsNone

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents

Europe - BE Page 8/10

Revision date 30-Apr-2020

BOSTIK ARDACOLOR FLEX MEDIUM GREY

Supercedes Date: 19-Mar-2020 Revision Number 1.03

_

at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Cement, portland, chemicals (Chromium VI reduced)	65997-15-1	item 47

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National Regulations

<u>France</u>

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Cement, portland, chemicals (Chromium VI reduced)	RG 8,RG 10 RG 8
65997-15-1	

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

TRGS - 510 Storage Class Storage Class 13 : Non-combustible solids

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

15.2. Chemical safety assessment

Europe - BE Page 9/10

BOSTIK ARDACOLOR FLEX MEDIUM GREY

Supercedes Date: 19-Mar-2020

•

Revision date 30-Apr-2020

Revision Number 1.03

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation

H318 - Causes serious eye damage H335 - May cause respiratory irritation

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 30-Apr-2020

Indication of changes

Revision note SDS sections updated, 1.

Training Advice When working with hazardous materials, regular training of operators is required by law

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Europe - BE Page 10/10